

20' Low Spec. (low specification)

HANBAO's Prefix for this type: HBTU





Dimension

External (mm)	Length 6,058
	Width 2,438
	Height 2,591
Internal (mm)	Length 5,898
	Width 2,352
	Height 2,393
Door	Width 2,340
Opening (mm)	Height 2,280

Internal Capacity

33.2 CBM.

Ratings (kgs)

Max. Gross Weight	30,480
Tare Weight	2,100
Max. Payload	28,380

Paint

Exterior:

Epoxy zinc rich primer	20 mic. DFT.
Zinc epoxy primer	40 mic. DFT.
Acrylic top coat	30 mic. DFT.
Total	90 mic. DFT.

Interior:

Epoxy zinc rich primer	20 mic. DFT.
Epoxy high build	50 mic. DFT.
Total	70 mic. DFT.

Undercoating

Epoxy zinc rich primer	20 mic. DFT.
Bituminous undercoating	150 mic. DFT.
Total	170 mic. DFT.

Roof panel:

1.6mm thick die-stamped steel sheets.

Side wall:

The trapezium section side wall is constructed with 1.6mm thick fully vertically continuous-corrugated steel panels at the intermediate area and 2.0mm thick fully vertically continuous-corrugated steel panels at both ends which are butt welded together to form one panel and continuously welded to the side rails and corner posts.

Floor: 28mm plywood floor.