

20' Open Top (OT): 20' x 8' x 8'6''



Characteristics

Soft detachable roof tarpaulin; for machinery requiring top loading and over height cargo.

Reinforced bottom side rails.

Dimension

External (mm)	Length	6,058
	Width	2,438
	Height	2,591
Internal (mm)	Length	5,898
	Width	2,352
	Height	2,698
Door	Width	2,340
	Opening (mm)	Height
Roof opening (mm)	Width between top side rails	2,252
	Length between top headers	5,397

Internal Capacity

32.5 CBM.

Ratings

Title	KGS
Max. Gross Weight	30,480
Tare Weight	2,200
Max. Payload	28,280

Transportation

The container is constructed to be suitable for transportation in normal operating conditions by modes of:

- A. Marine - in the ship cell guides, 8 high stacked; on the deck, 4 high stacked and secured by suitable vertical and diagonal wire lashings
- B. Rail - on the flat cars or special container car, secured by twistlocks or the equivalent at the four bottom corner fittings.
- C. Road - on flat or chassis secured by twistlocks or the equivalent at the four bottom corner fittings

Paint

Exterior:

Apply one coat of zinc rich primer to **30** mic. DFT.

Apply one coat of epoxy primer to **30** mic. DFT.

Apply one coat of Chlorinated rubber or Acrylic top coat to **50** mic. DFT.

Total **110** mic. DFT.

Interior:

Apply one coat of zinc rich primer to **30** mic. DFT.

Apply one coat of epoxy top coat to **50** mic. DFT.

Total **80** mic. DFT.

Undercoating

The whole underside is coated with **30** mic. of zinc rich primer and **200** mic. of Waxy or Bituminous undercoating.

Total **230** mic. DFT.

Technical Data

Material	Corten Steel
floor	28mm plywood floor
Classification Society	Germanischer Lloyd or Bureau Veritas
Regulations & Standards	ISO/TC-104, TIR, TCT, UIC, CSC
Paint Supplier	Hempel
Outside colour	RAL 5010
Inside colour	RAL 5010

Other Modifications per Request

- own prefix and serial numbers
- own nomination of colours
- hardtop

