

40' Double Door (DD): 40' x 8' x 8'6"



Characteristics

Doors at both ends. Cargo can be loaded or unloaded from both ends.

Dimension

External (mm)	Length	12,192
	Width	2,438
	Height	2,591
Internal (mm)	Length	11,978
	Width	2,352
	Height	2,393
Door	Width	2,343
	Opening (mm) Height	2,280

Internal Capacity

67.4 CBM.

Ratings

Title	KGS
Max. Gross Weight	30,480
Tare Weight	3,800
Max. Payload	26,680

Transportation

The container is constructed to be suitable for transportation in normal operating conditions by modes of:

- A. Marine - on deck or in cell guided by vertical or diagonal lashings
- B. Rail - on flat or container car secured at its bottom corner fittings
- C. Road - on flat or chassis secured at its bottom corner fittings

Paint

Exterior:

Apply one coat of zinc rich primer to **30** mic. DFT.

Apply one coat of epoxy primer to **40** mic. DFT.

Apply one coat of Chlorinated rubber or Acrylic top coat to **40** mic. DFT.

Total **110** mic. DFT.

Interior:

Apply one coat of zinc rich primer to **25** mic. DFT.

Apply one coat of epoxy top coat to **50** mic. DFT.

Total **75** mic. DFT.

Undercoating

The whole underside is coated with **25** mic. of zinc rich primer and **200** mic. of Waxy or Bituminous undercoating.

Total **225** mic. DFT.

Technical Data

Material	Corten Steel
floor	28mm plywood floor
Classification Society	Germanischer Lloyd or Bureau Veritas
Regulations & Standards	ISO, TIR, TCT, UIC, CSC
Paint Supplier	Hempel
Outside colour	RAL 5010, 3009, 9010 with pu coating
Inside colour	RAL 7035

Other Modifications per Request

- own prefix and serial numbers
- own nomination of colours
- lashing strips, lashing rings
- more ventilators
- varnished floor
- bamboo floor

